



US009658023B1

(12) **United States Patent**
Powell

(10) **Patent No.:** **US 9,658,023 B1**
(45) **Date of Patent:** **May 23, 2017**

(54) **HAND HELD THROWING APPARATUS AND METHOD**

(71) Applicant: **Richard Powell**, Austin, TX (US)

(72) Inventor: **Richard Powell**, Austin, TX (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/684,761**

(22) Filed: **Apr. 13, 2015**

Related U.S. Application Data

(60) Provisional application No. 62/023,992, filed on Jul. 14, 2014.

(51) **Int. Cl.**
F41B 3/03 (2006.01)
F41B 3/00 (2006.01)

(52) **U.S. Cl.**
CPC **F41B 3/005** (2013.01)

(58) **Field of Classification Search**
CPC F41B 3/03; F41B 3/005; F41B 7/00; F41B 11/642

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 970,018 A * 9/1910 Coleman F41B 7/006 102/371
- 1,091,512 A * 3/1914 Hoffman A63B 69/408 124/36
- 1,268,187 A * 6/1918 Velk A63B 69/408 124/7
- 1,287,780 A * 12/1918 Stanard F41B 11/642 124/66

- 1,381,639 A * 6/1921 Hess F41B 7/00 124/26
- 1,457,674 A * 6/1923 Kennedy A01M 3/027 124/36
- 1,726,534 A * 9/1929 Berger F41B 7/003 124/2
- 1,841,390 A * 1/1932 Welch F41B 3/03 124/7
- 2,318,139 A * 5/1943 Calabrese F41B 3/03 124/35.1
- 4,719,897 A * 1/1988 Gaudreau F41B 5/1469 124/25
- 4,774,786 A * 10/1988 Zarembo A01M 3/027 124/18
- 4,827,894 A * 5/1989 Schallberger F41B 5/12 124/25
- 5,979,424 A * 11/1999 Alvarez F41B 7/08 124/16

(Continued)

Primary Examiner — Melba Bumgarner

Assistant Examiner — Amir Klayman

(74) *Attorney, Agent, or Firm* — J. Nevin Shaffer, Jr.

(57) **ABSTRACT**

A hand held throwing apparatus and method includes of a U-shaped body with two sides and a bottom forming an open interior, the U-shaped body having an open front and an open back. A combination throwing-cocking arm with a first end and a second end is provided where the second end is rotatably connected with the U-shaped body in proximity to the open front in between the two sides. A spring is provided with a first end and a second end, where the first end of the spring is attached to the second end of the combination throwing-cocking arm and the second end of the spring is connected with the U-shaped body. A stop device is attached to the combination throwing-cocking arm between the first end and the second end and a handle is connected to the U-shaped body.

16 Claims, 5 Drawing Sheets

